

VIP1113

IP SET-TOP BOX WITH MINIMALIST DESIGN FOR HIDDEN INSTALLATIONS

Broaden your customer base and generate revenue with our new, innovative IP set-top box. VIP1113 is our smallest IPTV client ever. Equipped with an RF transceiver, the VIP1113 can be placed behind the TV set, leaving all user interaction to the remote control.

Product Overview

The innovative VIP1113 broadens Motorola's IPTV client portfolio. The VIP1113 is a feature-rich yet compact set-top box that users can place behind their TV sets or in a concealed location, while still enjoying high-quality IPTV services such as high-definition broadcast TV, timeshift, on-demand and interactive applications, as well as OTT services. The VIP1113's compact design minimizes energy consumption, keeping costs down and reducing its impact on the environment.

Powered by the KreaTV operating system

VIP1113 is powered by the Motorola KreaTV operating system, which integrates with leading VOD, middleware, and Conditional Access (CA) systems. KreaTV provides open, well-defined Application Programming Interfaces (APIs) for application development and customization. The KreaTV Software Developer's Kits (SDKs) offer operators, as well as third-party integrators, a fast track to high-quality, revenue-generating digital TV offerings and value-added social media services.



Features and Benefits

- Compact HD IP set-top box
- Innovative, sleek design
- Cost-effective, environmental-friendly
- wall-mountable
- RF RCU for hidden installations
- Micro SD card reader for local timeshift functionality
- Powered by the KreaTV operating system for openness, flexibility, and smooth systems integration



Specifications

PROCESSING	
CPU	667 MHz/1200 DMIPS
DRAM	256 (512) MB DDR3
Flash	64 (128) MB
VIDEO INTERFACES	
Digital video	HDMI with HDCP
Analog video	CVBS
Video codecs	MPEG-2, MPEG-4 AVC (H.264) Other codecs on request
VIDEO RESOLUTION	
PAL	576i, 576p
High definition	720p, 1080i, 1080p(60)
AUDIO INTERFACE	
Analog audio	3.5 mm jack R+L, combined with video
Audio codecs	Dolby® Digital, MPEG-1 (MUSICAM), MP3, AAC LC, HE-AAC Other codecs on request
OTHER INTERFACES	
Ethernet	10/100 Base-T Ethernet (RJ45)
RF transceiver for remote	RF4CE
USB	1 x USB 2.0
Micro SD reader	For local timeshift TV

PHYSICAL	
Dimensions	130x130x23 mm
Weight	~160 g
POWER	
DC power switch	Yes
Power supply	External power supply 5 V/1.5 A
Power consumption	~5 W
OPERATING ENVIRONMENT	
Temperature	0°C to 40°C (32°F to 104°F)
Humidity	8% to 95% (non-condensing)
COMPLIANCE	
RoHS, CE and WEEE	
SOFTWARE	
Operating system	Motorola KreaTV 4.5 or later
MW/UI	Integrated with Motorola Dreamgallery and other MW/UI systems. SDKs for integration and development.
CA/DRM	Integrated with Motorola SecureMedia and other CA/DRM systems. SDKs for integration and development.
Software upgrade	Remote software download

Specifications are subject to change without notice.

For more information, visit www.motorola.com

